



- 1.Design conforms to AS2638.2 .
- 2.Face to Face according to AS2638.2.
- 3.Flanges drilling according to AS4087 PN16.
- 4.Pressure test according to AS2638.2.

600	508	825	756	16-30	720	42	5	1320	800
500	457	705	641	16-26	609	35	4	1120	800
450	432	640	584	12-26	552	33	4	1045	560
400	406	580	521	12-26	489	33	4	970	560
375	381	550	495	12-26	463	33	4	880	450
350	381	525	470	12-26	438	33	4	790	450
300	356	455	406	12-22	378	30	4	695	450
250	330	405	356	8-22	328	24	3	605	450
225	305	370	324	8-18	300	24	3	560	320
200	292	335	292	8-18	268	23	3	515	320
150	267	280	235	8-18	211	23	3	410	280
100	229	215	178	4-18	154	20	3	315	200
80	203	185	146	4-18	122	18	3	290	200
65	190	165	127	4-18	103	18	3	280	180
50	178	150	114	4-18	90	18	3	270	180
DN	L	D	D1	n-d	D2	b	f	H	W
			AS4087 PN16						

14	Handwheel	Ductile Iron		
13	Dust Guard	EPDM		
12	O-Ring	EPDM		
11	Bonnet Gland	Ductile Iron		
10	O-Ring	EPDM		
9	Washer	Nylon		
8	Up sealing	EPDM		
7	Bonnet	Ductile Iron		
6	Bolt	SS(DN50-DN300)		
		Galvanized steel (DN350-DN600)		
5	Bonnet Gasket	EPDM		
4	Stem Nut	Brass		
3	Stem	SS420		
2	Wedge	Ductile Iron +EPDM		
1	Body	Ductile Iron		
No.	Part	Material		
DRN	Wang	WEIGHT	MATERIAL	
CHK		SCALE	Gate Valve	
APP		DATE		
hiwa			CZ0019	
			REV	240719a

This document is the property of Huihua Valve Industry Co.
 Distribution of this document without the written consent of the owner is strictly forbidden
 Failure to comply will incur a liability for damages

<http://www.hiwa.cn> Website
sales@hiwa.cn Email

86-533-6077200 Phone
 86-533-6077233 FAX

Huihua Valve Industry co.
 No.36 MinAn Road New Hi-Tech Industry
 Zone Zibo Shandong China 255088 p.c