



Design standard: EN1349/EN1074-5
 Face to Face: EN1349:2000/1074-2000
 Flange Drilling: EN1092-2-PN10/PN16
 Pressure Test: EN12266, API598, ISO5208
 This valve is a pressure reducing valve used to maintain
 line pressure.

DN	L	D	D1	EN1092-2-PN10		EN1092-2-PN16		b
				D0	n×φd	D0	n×φd	
50	230	165	99	125	4×19	125	4×19	19
65	290	185	118	145	4×19	145	4×19	18
80	310	200	132	160	8×19	160	8×19	18
100	350	220	156	180	8×19	180	8×19	18
150	480	285	211	240	8×23	240	8×23	18
200	600	340	266	295	8×23	295	12×23	20
250	730	400	319	350	12×23	355	12×28	22
300	850	460	370	400	12×23	410	12×28	24.5

DN	WEIGHT	MATERIAL	
DN	SCALE		
APP	DATE		
			07/02/2020
dashpot check valve			

Hiwa

CM0007

REV 20200204

This document is the property of Hiwa Valve Industry Co.
 Distribution of this document without the written consent of the owner is strictly forbidden
 Failure to comply will incur a liability for damages

<http://www.hiwa.cn> Website
 sales@hiwa.cn Email

98-533-8077200 Phone
 98-533-8077233 FAX

Hiwa Valve Industry Co.
 No.36 Minlin Road New Hi-Tech Industry
 Zone Zibo Shandong China 255008 p.c.