



Design:BS 3464.
 Face to Face:BS 3464.
 Flange drilling:BS10 Table D/E
 Hydraulic test to ISO 5208.

DN	L	ØD	BS10 Table D		BS10 Table E		b	H	W
			ØD1	n-Ød	ØD1	n-Ød			
DN50	146	155	114	4-18	114	4-18	16	245	180
DN65	160	175	127	4-18	127	4-18	17	265	180
DN80	165	185	146	4-18	146	4-18	18	302	200
DN100	172	210	178	4-18	178	8-18	18	338	200
DN125	191	254	210	8-18	210	8-18	20	418	280
DN150	210	280	235	8-18	235	8-22	22	459	280
DN200	241	337	292	8-18	292	8-22	22	549	320

Item	Part Name	Material	Q'ty	Remark
15	Handwheel	Ductile iron		
14	Dust ring	NBR		
13	Bolt	Carbon steel		
12	Gland	Ductile iron		
11	O-ring	NBR		
10	Nylon washer	Nylon		
9	V-ring	NBR		
8	Stem	SS420		
7	Bonnet	Ductile iron		
6	Bonnet gasket	Graphite		
5	Stem nut	Brass		
4	Wedge	Ductile iron		
3	Wedge ring	Brass		
2	Seat ring	Brass		
1	Body	Ductile iron		

DRN	wang	WEIGHT		MATERIAL
CHK		SCALE		Gate Valve
APP		DATE	07/25/2024	
				CZ0042
				REV

Huihua Valve Industry Co.
 No.36 MinAn Road New Hi-Tech Industry Zone Zibo Shandong China 255088 p.c
 Phone 86 - 533 - 6077200 FAX 86 - 533 - 6077233
 Website http://www.hiwa.cn Email sales@hiwa.cn
 This document is the property of Huihua Valve Industry Co.
 Distribution of this document without the written consent of the owner is strictly forbidden
 Failure to comply will incur a liability for damages